



XP Clamshell Swivel Pipe Fittings

When using APT product piping, continuous runs eliminate the need for in-line joints. Installers make connections inside accessible containment sumps using APT's swivel fittings. These fittings are manufactured from solid brass or stainless steel with two Viton O-rings protected in grooves located on the inside of the connector. Plated clamps secure the fittings to the pipe. XP Series pipe clamps are labeled XP for easy identification.

Note: Use only XP Series fittings with XP piping.

Features & Benefits

Feature

- No special tools required.

Benefit

- No project delays when swage machine is inoperative.

Feature

- NPT Threads.

Benefit

- Fast and secure installation.
- Fittings available locally.
- Field proven.



Brass Swivels

MODEL	DESCRIPTION
MS-XP-150-150	Installs on the end of 1 1/2" single/secondary contained XP pipe with 1 1/2" NPT
MS-XP-175-200	Installs on the end of 1 3/4" single/secondary contained XP pipe with 2" NPT
MS-XP-200-200	Installs on the end of 2" single/secondary contained XP pipe with 2" NPT

Stainless Steel Swivels

MODEL	DESCRIPTION
MS-XP-150-150SS	Installs on the end of 1 1/2" single/secondary contained XP pipe with 1 1/2" NPT
MS-XP-175-200SS	Installs on the end of 1 3/4" single/secondary contained XP pipe with 2" NPT
MS-XP-200-200SS	Installs on the end of 2" single/secondary contained XP pipe with 2" NPT

Male Swivel - XP Series

MODEL	DIM. "A"	DIM. "B"	DIM. "C"
MS-XP-150-150	4.00"	4.00"	1.75"
MS-XP-175-200	4.00"	4.00"	1.75"
MS-XP-200-200	4.50"	4.75"	2.25"

